








Product Overview 2015 Options and Configurations for Cabinets

Sketch	Type Designation	Description	Cabinet Series						
Materialoptionen									
	GO	Reduced surface resistance , antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0	all						
	F 30	Fire resistance class F 30 , as per DIN 4102, if installed on customer-supplied base plate	CLASSIC						
	Exp	Preparation for a pressurized cabinet to DIN EN IEC 60079-2 Pressure test with inspection certificate	CLASSIC						
Door stays (door aperture angle 105°)									
	STAF-VZ	Door stay with lock-open device	Galvanized steel						
	STAF-EA4	Door stay with lock-open device	Stainless steel						
	STAT	Telescopic door dampener with adjustable manual brake							
	STAG-VZ	Gas strut, automatically pushes the door open	Galvanized steel						
	STAG-E	Gas strut , automatically pushes the door open	Stainless steel						
Wind and weather protection									
	Roof extension (500 mm) with lateral wind protection covers								
	CLASSIC SDWC	Price	Cabinet width (mm)						
			700	900	1100	1350	1550	1750	1950
		Series 110							
		Series 135							
		Series 160							
		Series 185							
	Series 210								
	BASIC SDWB	Price	Cabinet width (mm)						
			640	840	1040	1290	1490	1690	1890
		Series 100							
		Series 125							
Series 150									
Series 175									
Series 200									
Lifting lugs									
	SK002	Installed on the roof, removable type, suitable for empty cabinet or slight additional on the mounting plate; payload 50 kg	Set = 2 pcs	CLASSIC					
	SK004			BASIC					
	SK003	Installed on the roof, removable type, for loads of 250 kgs	Set = 4 pcs	CLASSIC					
	SK005	Installed on the roof, removable type, suitable for loads of 200 kgs, extra pair of mounting rails required, see page 3.		BASIC					
	SKOD-M10	Installed on the roof, with tension rods, suitable for loads of 600 kgs, in case of floor version A for 300 kgs	only with stainless steel floor frame	CLASSIC					
	SKOD-M16	Installed on the roof, with tension rods, suitable for loads of 1,200 kgs							
	SK008-WSA	Lifting and mounting brackets on the floor frame, maximum load 3.000 kg		CLASSIC					
	SK0082-WSA	Crane- & mounting bracket "heavy lift" at the groundborder, charge on request		CLASSIC					



Product Overview 2015 Options and Configurations for Cabinets

Aluminium frame window with Makrolon glass window, lockable (installation height 39 mm)										
	SF012	Dimensions 400 x 400 mm				excl. Recess	CLASSIC BASIC			
	SF013	Dimensions 600 x 400 mm								
	SF014	Dimensions 800 x 415 mm								
	SF015	Dimensions 800 x 615 mm								
	SF016	Dimensions 800 x 450 mm								
	SF017	Dimensions 800 x 800 mm								
GRP sunshades in sandwich construction, installed over the standard roof										
	SD003	c/w spacers of up to 20 mm maximum					all			
		c/w spacers of > 20 and < 150 mm								
Special designs for analyzer cabinets										
	SA030	Horizontal partition, with one-piece door Partition top / bottom 1000/ 1000 mm					CLASSIC BR 210, BASIC BR 200			
	SA029	Horizontal partition, with two separate doors Partition top / bottom 1000 / 1000 mm								
Equipment for bottle storage cabinets										
	SGOP	Bottle holder in rigid PU-foam with nylon strap, for bottles of up to 225 mm diameter				extra mounting rails see page 3		all		
	SGOE	Bottle holder with stainless steel mounting chain of 600 mm length, for bottles of up to 300 mm diameter								
	SGOE-250	Universal bottle holder, adjustable, with stainless steel mounting chain								
Loading ramp foldable with raised inner floor (aluminium)										
	CLASSIC SGOO	Price		Cabinet width (mm)						
				700	900	1100	1350	1550	1750	1950
		Depth (mm)	500							
			700							
			900							
	1100									
	BASIC SGOO	Price		Cabinet width (mm)						
				640	840	1040	1290	1490	1690	1890
		Depth (mm)	300							
			400							
600										
800										
1000										

Subject to technical changes, printing errors and price increases due to rising raw material costs. Not all the options can be combined.

The listed prices are ex works (INCOTERMS 2010), uncleared, packing extra, plus V.A.T. (if applicable).

Prices are subject to change without notice.

Payment: 10 days 2 %, 30 days net.

Place of performance is Neustadt on the Donau and place of jurisdiction is Ingolstadt on the Donau, Germany



Product Overview 2015 Options and Configurations for Cabinets

additional Mounting rails (MS)					
	Vertically mounted				
	Ordering designation / Price		Material		
			Anodized aluminium	Stainless steel	Galvanized steel
	BASIC series 100/ CLASSIC series 110		SMSA-980	SMSV-980	SMSS-980
	BASIC series 125/ CLASSIC series 135		SMSA-1230	SMSV-1230	SMSS-1230
	BASIC series 150/ CLASSIC series 160		SMSA-1490	SMSV-1490	SMSS-1480
	BASIC series 175/ CLASSIC series 185		SMSA-1730	SMSV-1730	SMSS-1730
	BASIC series 200/ CLASSIC series 210		SMSA-1980	SMSV-1980	SMSS-1980
CLASSIC series 250		SMSA-2380	SMSV-2380	SMSS-2380	
	Horizontally mounted				
	Ordering designation / Price		Material		
			Stainless steel	Galvanized steel	
	Related to the size of the wall panels *	Width (mm)	400	SMSV-400	SMSS-400
			600	SMSV-600	SMSS-600
			800	SMSV-800	SMSS-800
			1000	SMSV-1000	SMSS-1000
	One-piece over the entire length	Width (mm)	1350	SMSV-1350	SMSS-1350
			1550	SMSV-1550	SMSS-1550
			1750	SMSV-1750	SMSS-1750
1950			SMSV-1950	SMSS-1950	
Other length upon request					
* Particularly for BASIC cabinets: in case of laterally-positioned horizontal mounting rails additional vertical rails are required behind the door (see table above)					
Earthing/grounding components					
	SPOT-I	Equipotential bonding till width 2150 mm			
	SPOT-I	Equipotential bonding for bigger cabinets			
	FP062	Equipotential bonding with copperrails 30 x 5 mm			
	SZ117	Lightning protection			
Entries for cable glands and pipe fittings					
	Price	Recess with laminated reinforcement	Recess with removable flange plate		Wandelement massiv
			GFP 4 mm thick	Stainless steel 2 mm thick	
	100 x 100 mm				
	200 x 100 mm				
	300 x 200 mm				
	200 x 200 mm				
400 x 200 mm					
Other dimensions upon request					
SXKL	Cable entry flap with stainless steel frame 200 x 200 mm with internal locking				CLASSIC BASIC