

700 Series

UHP Stainless Steel Bulk Facility Valve
High Flow Bellows

aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding

Value Proposition:

The Ultra High Purity (UHP) 700 Series high flow valve offers high purity and high flow for UHP gas distribution systems. The unique design reduces valve weight and, as a result, lowers installation costs.

All Parker UHP bellows valves use a full flow bore that positions the bellows assembly out of the flow path when the valve is open.



Contact Information:

Parker Hannifin Corporation
Veriflo Division
250 Canal Blvd
Richmond, California 94804

phone 510 235 9590
fax 510 232 7396
veriflo.sales@parker.com

www.parker.com/veriflo
Mobile App: m.parker.com/veriflo

Product Features:

- Inconel 625 bellows for increased pressure, ultra high purity and maximum cycle life in a small envelope
- Lower weight reduces gas distribution system installation costs
- Optimized stroke for higher Cv
- Optimum purge port locations at seals
- Maximum operating pressure 375 psig (250 psig 1" size)
- Sizes up to 6" available
- AOP available in 1", 1-1/2" and 2" sizes




ENGINEERING YOUR SUCCESS.


700 Series

Dimensional Drawing

1" - 4" VALVE (AOP 1", 1-1/2" and 2" only. See dimensional specifications below.)



6" VALVE (See dimensional specifications below.)



DIMENSION TABLE									
Part (Manual)	Size Body	C _v	A (inch)	B (inch)	C (inch)	D (inch)	E (inch)	F (inch)	Weight (lbs)
UHP0706	1"	19 (b)	8.49	1.00	7.2	1.50	4.00	3.93	3.2
UHP0708	1.5"	41 (a)	10.00	1.50	7.9	2.00	5.00	3.86	5.0
UHP0712	2"	86 (a)	13.26	2.00	10.6	3.00	6.00	5.59	11.5
UHP0716	3"	206 (b)	16.00	3.00	13.7	4.00	8.00	7.21	23.0
UHP0724-32	4"	317 (b)	20.00	4.00	18.8	5.00	10.00	10.94	36.0
UHP0724-48	4"	294 (b)	32.98	6.00	19.8	5.00	10.00	10.94	40.4

DIMENSION TABLE									
Part (AOP)	Size Body	C _v	A (inch)	B (inch)	C (inch)	D (inch)	E (inch)	F (inch)	Weight (lbs)
UHP0706-A	1"	19 (b)	8.49	1.00	13.7	1.50	6.00	3.93	20.7
UHP0708-A	1.5"	39 (a)	10.00	1.50	16.4	2.00	6.00	3.86	31.0
UHP0708-F	1.5"	41 (a)	10.00	1.50	13.2	2.00	5.99	3.86	19.0
UHP0712-B	2"	82 (a)	13.26	2.00	14.1	3.00	6.99	5.59	25.0
UHP0712-F	2"	86 (a)	13.26	2.00	16.7	3.00	7.50	5.59	36.0

a) Test procedures per ANSI/ISA S75.02-1998 and SEMI F32-0998.

b) C_v values estimated by computational fluid dynamics analysis.

Safety Guide and Installation and Operating Instructions available at
www.parker.com/veriflo

700 Series

Ordering Information

Build a 700 Series valve by replacing the numbered symbols with an option from the corresponding tables below.

Color Explanations: Black = Standard Lead Time Configurations
Blue = Extended Lead Time Configurations

For an explanation of Ordering options please reference literature 25000275 at www.parker.com/veriflo

Sample: **UHP** **0712** **C** **1** **1616** **10** **A** **S** **K**

Finished Order: **UHP0712C1161610ASK**

1 Basic Series
0706 = 1" 1/4" purge port size
0708 = 1.5" 1/4" purge port size
0712 = 2" 1/2" purge port size
0716 = 3" 1/2" purge port size
0724 = 4" & 6" 1/2" purge port sizes

2 Purge Port
C = Up & downstream

Note: Purge Valves ordered separately:
1", 1-1/2": 830LSFSFM (54019556)*
2", 3", 4" & 6": 855LSFS8FM (54019557)*
* 830LSFSFM limited to 300 psig max,
855LSFS8FM limited to 250 psig max.
If high pressure purge valves are required,
please contact the factory.

3 Operation
Manual Actuation
1 = Blue
Pneumatic Actuation
A = Normally Closed - 0706 and 0708 Only.
B = Double Actuation - 0712 Only.
F = Normally Open - 0708 and 0712 Only.
Consult Factory for additional Handle Colors

4 Port Size
0808 = 1" - 0706 Only.
1212 = 1 1/2" - 0708 Only.
1616 = 2" - 0712 Only.
2424 = 3" - 0716 Only.
3232 = 4" - 0724 Only.
4848 = 6" - 0724 Only

5 Internal Surface Finish
10 = 10 Ra

6 Design Series
A = Standard Design

7 Purge Port Type
S = Standard face seal fitting

8 Seat Material
K = PCTFE

Additional configurations available upon request



High Flow, Value Priced Valve
for High Purity Gas Systems

700 Series

Specifications

Materials of Construction	
Wetted	
Body	316L Stainless Steel
Tube Ends	316L Stainless Steel
Seat Holder	
0706	316 Stainless Steel
0708, 0712, 0716, 0724	316L Stainless Steel
Bellows Adapter	316L Stainless Steel
Bellows	
0706	316L Stainless Steel
0708, 0712, 0716, 0724	Inconel® 625
Seat	PCTFE
Bonnet Gasket	Nickel
Non-wetted	
Handle	Aluminum
Stem	316L or 17-4 Stainless Steel
Driver	Bronze
Guide	Brass
Bonnet	Aluminum
Surface Finish	10 micro inch Ra
Weight	See Dimension Tables

For additional information on materials of construction, functional performance and operating conditions, please contact factory.

Notes:

- A - Valves shall be installed and supported in accordance with ASME B31.3 - 1996, Chapter II, Part 5, Flexibility and Support or equivalent.
- B - Rated for external leak test at 110% (412.5 psig), valve in open position.
- C - Rated for external leak test at 110% (275 psig), valve in open position for 0706 only.

Functional Performance	
Design Pressure	
Proof	
0706	375 psig (25.86 barg)
0708, 0712, 0716, 0724	562.5 psig (38.78 barg)
Burst	
0706	750 psig (51.71 barg)
0708, 0712, 0716, 0724	1,125 psig (77.57 barg)
Installation	See note A
Flow Capacity	See Dimensional Table
Leak Rate	Inboard Test Method
Internal	
Rated	1 X 10 ⁻¹⁰ scc/sec He
Std Production	1 X 10 ⁻⁹ scc/sec He
External (See notes B & C)	1 X 10 ⁻¹⁰ scc/sec He
Operating Conditions	
Maximum Pressure	
0706	250 psig (17.24 barg)
0708, 0712, 0716, 0724	375 psig (25.86 barg)
Minimum Pressure	Vacuum
AOP Actuation Pressure	100 psig (6.9 barg, nominal)
AOP Air Inlet	1/8 - 27 NPT
Temperature	
Maximum	140°F (60°C)
Minimum	-40°F (-40°C)

Inconel® is a registered trademark of Special Metals Corporation

OFFER OF SALE:

The items described in this document are hereby offered for sale by Parker-Hannifin Corporation, its subsidiaries or its authorized distributors. This offer and its acceptance are governed by the provisions stated in the detailed "Offer of Sale" elsewhere in this document or available at www.parker.com/veriflo



FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE. THIS DOCUMENT IS FOR REFERENCE ONLY. PLEASE CONSULT FACTORY FOR LATEST PRODUCT DRAWINGS AND SPECIFICATIONS

This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise.

The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors.

To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems.

The products described herein, including without limitation, product features, specifications, designs, availability and pricing are subject to change by Parker Hannifin Corp and its subsidiaries at any time without notice.

Proposition 65 Warning: This product contains chemicals known to the state of California to cause cancer or birth defects or other reproductive harm.

© 2007 Parker Hannifin Corporation



Use mobile device to scan this QR Code.

LitPN: 25000209

Rev: J

Date of Issue 08/2013



ENGINEERING YOUR SUCCESS.